

RANGER



■ **Class leading design with more possibilities**





Turbofiller High capacity filler 25 or 35 litre



External cleaning



Brakes Hydraulic or pneumatic



HC5500 Powerful controller with large 4 line display



VP booms from 20 to 24 metres

The booms are constructed in steel with a lattice design optimizing weight with the greatest possible strength. An anti-yaw device is incorporated into the boom centre to minimise any movement of the boom. The excellent performance of the PRO VP boom ensures precision spray applications even in the most challenging of field conditions.

All boom functions on the PRO VP can be electro-hydraulically operated, from a compact conveniently located control panel. The primary controls, those which are most used in the field, are grouped together for ease of use, such as boom height, independent tilting of either boom section and complete boom slanting.

The compact boom gives big flexibility in folding and manoeuvring in fields with obstacles.



SelfSteer

SelfSteer is coupled on the tractor's 3-point hitch and gives a better tracking on headland.

SelfSteer is a simple mechanical steering system with low maintenance and no operation or setting required by the operator during the spray job.

Slope correction

SelfSteer can be equipped with slope correction. Slope correction is manually operated directly from the tractor's hydraulics and helps the SelfSteer to stay in the tramline also in hilly conditions.

These new features really put the RANGER in its own class with even more possibilities for vegetable and special crop growers.

HARDI INTERNATIONAL A/s

Helgeshøj Allé 38 • DK 2630 • Taastrup • Denmark
E-Mail: hardi@hardi-international.com • www.hardi-international.com



HARDI reserves the right to change the specifications without notice. Illustrations shown may include optional extras and accessories.